

Excelsior-Flo Low Pressure Single Stage Regulators

MEGR-230 SERIES


DESCRIPTION

The MEGR-230 single-stage regulators are approved for use in small portable applications and outdoor cooking appliances utilizing low pressure.

NOTE: Single-stage regulators are not approved for RV use per NFPA 1192



SPECIFICATIONS

- Type:** Single Stage
- Orifice Diameter:** .059 Dia
- BTU Capacity:** 140,000 BTU (based on 25 PSI inlet @ 9" W.C. delivery pressure)
- Max. Inlet Pressure:** 250 PSI
- Inlet Connection:** 1/4" FNPT
- Outlet Connection:** 3/8" FNPT
- Exterior Finish:** Green Wet Coat
- Diaphragm:** Molded with O-Ring Bonnet / Body Seal
- Diaphragm Type:** Internal Relief - Spring Loaded
- Bonnet / Body Material:** Die Cast Aluminum
- Listings:**  LISTED / UL 144
- Mounting Holes:** 3-1/2" On Center



MEGR-230
Regulator with Drip Lip Vent



MEGR-231



MEGR-230-9
MEGR-230 with Soft-Nose
Excess Flow POL



Part No.	Description
MEGR-218	Single Stage Regulator - SN FF POL w/ Plastic Handwheel x 3/8" FNPT - 90° Vent
MEGR-230	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet
MEGR-230-9	Single Stage Regulator - SN .9 GPM Excess Flow POL Inlet x 3/8" FNPT Outlet
MEGR-230-90	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet - 90° Vent
MEGR-230-1618	Single Stage Regulator - Black F. QCC x 3/8" FNPT - 90° Vent
MEGR-230-1326	Single Stage Regulator - Black Female QCC Inlet (100,000 BTU/ H) x 3/8" FNPT Outlet
MEGR-231	Single Stage Regulator - Hardnose FF POL x 3/8" FNPT - 90° Vent