<u>100# MINI ASME, 200# & 420# PORTABLES</u>

Manchester

TC VS. ASME COMPARISON

- The TC 200#, 420# and ASME 100#, 200# & 420# cylinders can be transported with 80% of total container volume.

 Note: in BC a 420 ASME can only be transported with 5% max.
- The weight of an ASME 420# is 13 lbs. more than a [TC 420#. This thicker steel provides the customer greater longevity of the 420# assets.

• ASME code has a 25 year retest period in BC TC etest periods are 10 years in Canada

- State-of-the-art powder coating system cylinder finish, called "Armor Clad II -THE NEXT GENERATION," which improves the durability of the tank by 150%!
- Vacuum Pre-purged tank saves in the cost to prepare a tank for customer use.
- HDPE (High Density Polyethylene) Lids. Extremely durable rust-proof and dent-proof. So reliable, they come with a 10 year quarantee!

Propane Depot

3390 Lake City Way Burnaby BC V5A 3A6 ph:604-421-3108 info@propandepot.ca



aka 80 gallon, pig <u>TC</u> 450L

require a 10 year retest and can be transported full

ASME*

Lifting Lugs standard on 200# & 420#

*ASME tanks can only be transported with 5% or less and owner must take out a yearly permit for a fee and require a 25 year retest

***prices as of Sept.25/18....prices subject to change without notice

	Product Data			pane icities	Water Capacity	Length OL	Height H	Diameter D	Diameter B	Tare Weight	Skid Quantity	
Catalog No.		DOT	Lb	Gal	Lb	In	In	ln	In	Lb		
14205TC.11HL	200# DC	TC - Valve w/ Gauge	200	45.6	476	41.9	34.1	24	20.0	152	16	
1499TC.11HL	420#	4BW240 Vertical - Quickifit Valve	420	95.9	1000	53.8	45.6	30	23.1	278	9	
			kg	Liter	Kg	mm	mm	mm	mm	Kg		
14205TC.11HL	200#	4BW240 Vertical - Multi - Valve w/ Gauge	90.7	172.9	256.7	1064	865	610	508	66.7	16	
1499TC.11HL	420#	4BW240 Vertical - Quadrifitt Valve	190.5	363.0	453.6	1366	1159	762	587	126.1	9	
	ASME		Lb	Gal	Lb	In	In	ln	In	Lb		
68143HL	28.6 (10	0#) ASME MINI Vertical - 250 PSI 2 hole w/Gauge	100	22.9	238	37.1	29.8	18	15.5	85	20	
6765.11HL	57 gal. (200#) ASME Vertical - 250 PSI Multi Valve w/ Gauge		200	45.6	476	41.9	34.1	24	20.0	188	16	
6762.11HL	120 gal. (420#) ASME Vertical - 250 PSI Quadrifitt Valve		420	95.9	1000	53.8	45.6	30	23.1	291	9	
			Kg	Liter	Kg	mm	mm	mm	mm	Kg		
68143HL	28.6 (100#) ASME MINI Vertical - 250 PSI 2 hole w/Gauge		45.4	86.6	108.3	942	756	457	394	38.6	20	
6765.11HL	57 gal. (200#) ASME Vertical - 250 PSI Multi Valve w/ Gauge		90.7	172.9	256.7	1064	865	610	508	85.3	16	
6762.11HL	120 gal.	(420#) ASME Vertical - 250 PSI Quadrifitt Valve	190.5	363.0	453.6	1366	1159	762	587	132.0	9	